



# Powder Coated Midwall Split Unit Air Condiotners

| Specs                  | 9000 btu      | 12000 btu     | 18000 Btu     | 22000 btu      | 30000 btu     |
|------------------------|---------------|---------------|---------------|----------------|---------------|
| Cooling                | 2.5 kW        | 3.5 kW        | 5.1 kW        | 6.1 kW         | 8.8 kW        |
| Heating                | 2.8 kW        | 3.7 kW        | 5.61 kW       | 6.6 kW         | 9.2 kW        |
| Cooling Power Input    | 0.95 kW       | 1.25 kW       | 1.89 kW       | 2.19 kW        | 3 kW          |
| Heating Power Input    | 0.85 kW       | 1.2 kW        | 2.03 kW       | 2.09 kW        | 3.19 kW       |
| Cooling Current Input  | 4.2 A         | 5.6 A         | 8.9 A         | 9.5 A          | 13.6 A        |
| Heating Curretn Input  | 3.8 A         | 5.4 A         | 9.5 A         | 9.8 A          | 13 A          |
| <b>Indoor</b>          |               |               |               |                |               |
| Model                  | KFR-25G/Ec    | KFR-25G/Ec    | KFR-25G/Ec    | KFR-61G/Ec     | KFR-88G/Ec    |
| Power Supply           | 220 V / 50 Hz | 220 V / 50 Hz | 220 V / 50 Hz | 220 V / 50 Hz  | 220 V / 50 Hz |
| Airflow                | 500 >m3/h     | 576 >m3/h     | 686 >m3/h     | 750 >m3/h      | 1304 >m3/h    |
| Outside Spare Pressure | 0 Pa          | 0 Pa          | 0 Pa          | 0 Pa           | 0 Pa          |
| Dimensions LxWxH mm    | 790x270x180   | 790x270x180   | 940x270x180   | 1000x320x200   | 1235x325x250  |
| Packaging LxWxH mm     | 870x342x270   | 870x342x270   | 1007x340x275  | 1190x380x300   | 1445x410x320  |
| Noise                  | 29-39 dB(A)   | 29-39 dB(A)   | 43-45 dB(A)   | 43-47 dB(A)    | 49-51 dB(A)   |
| Gross Weight           | 10.5 kg       | 12 kg         | 14 kg         | 18.5 kg        | 25 kg         |
| Net Weight             | 8.5 kg        | 10 kg         | 14 kg         | 14 kg          | 18.5 kg       |
| <b>Outdoor</b>         |               |               |               |                |               |
| Model                  | KFR-25W/Ec    | KFR-25W/Ec    | KFR-51W/Ec    | KFR-35W/Ec     | KFR-88W/Ec    |
| Power Supply           | 220 V / 50Hz  | 220 V / 50Hz  | 220 V / 50Hz  | 220 V / 50Hz   | 220 V / 50Hz  |
| Airflow                | Air from top  | Air from top  | Air from top  | Air from top   | Air from top  |
| Compressor Model       | KS165VGBC     | RS221VDDC     | TS33VDEC      | PH371X3CS-4MU1 | LH53VBDC      |
| Qty (unit)             | 1             | 1             | 1             | 1              | 1             |
| Dimensions LxWxH mm    | 700x250x500   | 795x255x450   | 795x255x540   | 850x259x605    | 900x330x835   |
| Packaging LxWxH mm     | 825x320x550   | 920x335x595   | 920x335x595   | 995x415x690    | 1030x440x960  |
| Noise                  | 49 <dB(A)     | 52 <dB(A)     | 53 <dB(A)     | 55 <dB(A)      | 56 <dB(A)     |
| Gross Weight           | 29 kg         | 42 kg         | 42 kg         | 51 kg          | 80 kg         |
| Net Weight             | 25 kg         | 38 kg         | 38 kg         | 45 kg          | 65 kg         |
| <b>Gas</b>             |               |               |               |                |               |
| Material               | R22           | R22           | R22           | R22            | R22           |
| Charge                 | 0.61 kg       | 1.2 kg        | 1.2 kg        | 1.5 kg         | 2.48 kg       |
| <b>Dimensions</b>      |               |               |               |                |               |
| Liquid Pipe            | 6.35 mm       | 6.35 mm       | 6.35 mm       | 9.52 mm        | 9.52 mm       |
| Gas Pipe               | 9.52 mm       | 9.52 mm       | 9.52 mm       | 15.88 mm       | 16 mm         |
| Drain Pipe             | 15.2 mm       | 15.2 mm       | 15.2 mm       | 15.2 mm        | 15.2 mm       |

Powered by

**TOSHIBA**



**MITSUBISHI**

Compressors

